

285psi Shut Off Pressure

ANSI 150 Torque (in-lbs)				
SIZE	Wafer	Lug	Flanged	Buttweld
2"	310	310	310	310
2.5"	425	425	425	425
3"	690	690	690	690
4"	1,080	1,080	1,080	1,080
5"	1,655	1,655	1,655	1,655
6"	2,567	2,567	2,567	2,567
8"	5,134	5,134	5,134	5,134
10"	7,966	7,966	7,966	7,966
12"	12,922	12,922	12,922	12,922
14"	17,348	17,348	17,348	17,348
16"	26,022	26,022	26,022	26,022
18"	34,855	34,855	34,855	34,855
20"	44,414	44,414	44,414	44,414
24"	69,233	69,233	69,233	69,233

720psi Shut Off Pressure

ANSI 300 Torque (in-lbs)				
SIZE	Wafer	Lug	Flanged	Buttweld
2"	-	-	-	-
2.5"	-	-	-	-
3"	-	-	-	-
4"	2,089	2,089	2,089	2,089
5"	3,399	3,399	3,399	3,399
6"	4,691	4,691	4,691	4,691
8"	10,179	10,179	10,179	10,179
10"	17,313	17,313	17,313	17,313
12"	25,978	25,978	25,978	25,978
14"	36,537	36,537	36,537	36,537
16"	51,885	51,885	51,885	51,885
18"	70,808	70,808	70,808	70,808
20"	90,174	90,174	90,174	90,174
24"	162,637	162,637	162,637	162,637

1440psi Shut Off Pressure

ANSI 600 Torque (in-lbs)				
SIZE	Wafer	Lug	Flanged	Buttweld
2"	-	-	-	-
2.5"	-	-	-	-
3"	-	-	-	-
4"	-	-	-	-
5"	-	-	-	-
6"	-	-	-	-
8"	47,795	47,795	47,795	47,795
10"	61,603	61,603	61,603	61,603
12"	74,348	74,348	74,348	74,348
14"	100,760	100,760	100,760	100,760
16"	167,921	167,921	167,921	167,921
18"	270,292	270,292	270,292	270,292
20"	403,606	403,606	403,606	403,606
24"	584,166	584,166	584,166	584,166